

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2015 Revision: 27.10.2015

SECTION 1: Identification of the substance/mixture and of the company, undertaking

- · 1.1 Product identifier
 - · Trade name: Technovit Universal Liquid
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
 - · Application of the substance / the mixture Resin for indirect surface testing and impressions
- · 1.3 Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

Heraeus Kulzer GmbH

Grüner Weg 11, D-63450 Hanau

Tel.: +49 (0)6181 9689-2570 (Wehrheim)

- Informing department: email: technik.wehrheim@kulzer-dental.com
- · 1.4 Emergency telephone number:

Emergency CÓNTACT (24-Hour-Number):GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xn; Harmful

R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.

Xi: Irritant

R37/38: Irritating to respiratory system and skin.

Xi; Sensitising

R43: May cause sensitisation by skin contact.

F; Highly flammable

R11: Highly flammable.

R33: Danger of cumulative effects.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Page 2/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2015 Revision: 27.10.2015

Trade name: Technovit Universal Liquid

(Contd. of page 1)

· Hazard pictograms





GHS02

- · Signal word Danger
- · Hazard-determining components of labelling:
- methyl methacrylate
- · Hazard statements

H225 Highly flammable liquid and vapour.

H315 Căuses skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P243 Take precautionary measures against static discharge.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · 2.3 Other hazards
 - · Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
 - **Description:** Product based on methacrylates

- Description. I Todact based on		
 Dangerous components: 		
EINECS: 201-297-1 Reg.nr.: 01-2119452498-28-0000	methyl methacrylate Xi R37/38; Xi R43; F R11 Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	> 90%
EINECS: 202-805-4	N,N-dimethyl-p-toluidine T R23/24/25 R33-52/53 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT RE 2, H373; Aquatic Chronic 3, H412	0-5%
	a vigardinar of the listed viels physical refer to continu 10	

· Additional information For the wording of the listed risk phrases refer to section 16.

(Contd. on page 3)



Page 3/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2015 Revision: 27.10.2015

Trade name: Technovit Universal Liquid

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation Supply fresh air; consult doctor in case of symptoms.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing

Rinse out mouth and then drink plenty of water.

Instantly call for doctor.

In case of persistent symptoms consult doctor.

Product based on methacrylates

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
 - · Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
 - For safety reasons unsuitable extinguishing agents Water.
- · 5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
 - · Protective equipment: Put on breathing apparatus.
 - · Additional information -

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Prevent material from reaching sewage system, holes and cellars.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (diatomite, universal binders, for small amounts tissues).

Dispose of contaminated material as waste according to item 13.

Do not flush with water or aqueous cleansing agents

Send for recovery or disposal in suitable containers.

· 6.4 Reference to other sections

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

GB



Page 4/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2015 Revision: 27.10.2015

Trade name: Technovit Universal Liquid

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
 - Storage
 - Requirements to be met by storerooms and containers: Store in cool location.
 - · Information about storage in one common storage facility: Not required.
 - · Further information about storage conditions:
 - Store cool (not above 25 °C).

Store in cool, dry conditions in well sealed containers.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · 8.1 Control parameters
 - · Components with critical values that require monitoring at the workplace:

80-62-6 methyl methacrylate

OES Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

· DNELs

80-62-6 methyl methacrylate

worker industr., I.te., syst. 74.3 mg/Kg/d (human) Inhalative worker industr., I.te., syst. 210 mg/m3 (human)

· PNECs

80-62-6 methyl methacrylate

freshwater 0.94 mg/l (agua)

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
 - · Personal protective equipment

General protective and hygienic measures
Keep away from foodstuffs, beverages and food.
Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

Not neccessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

Protection of hands:

If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.

(Contd. on page 5)



Page 5/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2015 Revision: 27.10.2015

Trade name: Technovit Universal Liquid

(Contd. of page 4)

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:

 PVA gloves
- · For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Chloroprene rubber, CR

- · Eye protection: Safety glasses
- · Body protection: Light weight protective clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physic General Information	ical and chemical properties
· Appearance:	
· Form:	Fluid
· Colour:	Colourless
· Smell:	Characteristic
· Change in condition · Melting point/Melting rai · Boiling point/Boiling ran	
· Flash point:	10 ℃
· Ignition temperature:	430 °C
· Self-inflammability:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures is possible.
· Critical values for explosion	n:
· Lower:	2,1 Vol %
· Upper:	12,5 Vol %
· Steam pressure at 20 °C:	47 hPa
· Density at 20 °C	0.940 g/cm³
	(Contd. on page 6



Page 6/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2015 Revision: 27.10.2015

Trade name: Technovit Universal Liquid

(Contd. of page 5)

· Solubility in / Miscibility with

· Water: Not miscible or difficult to mix

· Viscosity:

· dynamic at 20 °C: 1 mPas

· Solvent content:

• **VOC USA** 911.9 g/l / 7.61 lb/gl

· VOC EU 911.9 g/l

• **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
 - · Conditions to be avoided: No decomposition if used and stored according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None
 - · Additional information:

If stored longer than recommended and/or above recommended temperature, product may polymerize generating heat.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
 - · Acute toxicity Based on available data, the classification criteria are not met.

•	LD/LC50	values	that are	relevant f	for classif	ication:
20.00	A 111		1 - 4 -			

80-62-6 methyl methacrylate

00 07 0 N N d'assathad as taladd'as				
	Inhalative	LC50/4 h	29.8 mg/l (rat)	
		LD50	>5000 mg/kg (rat) >5000 mg/kg (rab)	
	Oral	LD50	>5000 mg/kg (rat)	

99-97-8 N,N-dimethyl-p-toluidine

Oral LD50 500 mg/kg (rat) Inhalative LC50/4 h 1400 mg/l (rat)

- · Primary irritant effect:
 - Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
 - Germ cell mutagenicity Based on available data, the classification criteria are not met.
 - · Carcinogenicity Based on available data, the classification criteria are not met.
 - Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause respiratory irritation.

(Contd. on page 7)



Page 7/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2015 Revision: 27.10.2015

Trade name: Technovit Universal Liquid

(Contd. of page 6)

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
 - · Aquatic toxicity:

99-97-8 N,N-dimethyl-p-toluidine

LC50/96h 100 mg/l (fish)

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
 - · Additional ecological information:
 - · General notes:

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

- · 12.5 Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
 - · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Śmall quantities can be polymerized with the matching system component(s) and the cured solid material can be disposed of with the regular garbage. Larger quantities must be disposed of following the regulations of the local authorities.

- · European waste catalogue
- 11 01 98 other wastes containing dangerous substances
 - Uncleaned packagings:
 - · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN-Number · ADR, IMDG, IATA	1247	
· 14.2 UN proper shipping name · ADR	1247 METHYL METHACRYLATE MONOMER	
· IMDG, IATA	STABILIZED, solution METHYL METHACRYLATE MONOMER STABILIZED, solution	

(Contd. on page 8



Page 8/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2015 Revision: 27.10.2015

Trade name: Technovit Universal Liquid

(Contd. of page 7)

· 14.3 Transport hazard class(es)

· ADR



ClassLabel3 (F1) Flammable liquids.3

· IMDG, IATA



ClassLabel3 Flammable liquids.3

· 14.4 Packing group

· ADR, IMĎĞ, IAŤA //

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Flammable liquids.

Kemler Number: 339
• EMS Number: F-E,S-D

• 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

• UN "Model Regulation": UN 1247, METHYL METHACRYLATE MONOMER, STABILIZED, solution, 3, II

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

(Contd. on page 9)



Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.10.2015 Revision: 27.10.2015

Trade name: Technovit Universal Liquid

H331 H335 I H373 I	(Contd. of page 8) May cause an allergic skin reaction. Toxic if inhaled. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.
R23/24/25 7 R33 L R37/38 I R43 I R52/53 I	Highly flammable. Toxic by inhalation, in contact with skin and if swallowed. Danger of cumulative effects. Irritating to respiratory system and skin. May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
ADR: Accord euro International Carrie IMDG: International Carrie IMDG: International GHS: Globally Har EINECS: Europeal ELINCS: Europeal CAS: Chemical Ab VOCV: Lenkungs compounds) VOC: Volatile Orga DNEL: Derived No PNEC: Predicted N LC50: Lethal conclubories Lethal conclubories Lethal dose, PBT: Persistent, B VPVB: very Persist Flam. Liq. 2: Flam. Acute Tox. 3: Acut Skin Irrit. 2: Skin constitution Sens. 1: Sens STOT SE 3: Speci Aquatic Chronic 3:	péen sur le transport des marchandises dangereuses par Route (European Agreement concerning the age of Dangerous Goods by Road) al Maritime Code for Dangerous Goods I Air Transport Association monised System of Classification and Labelling of Chemicals In Inventory of Existing Commercial Chemical Substances In List of Notified Chemical Substances stracts Service (division of the American Chemical Society) sabgabe auf flüchtigen organischen Verbindungen, Schweis (Swiss Ordinance on volatile organic anic Compounds (USA, EU) -Effect Level (REACH) No-Effect Concentration (REACH) entration, 50 percent
· * Data compai	red to the previous version altered.